

Project	Type
Catalog #	

DESCRIPTION


The Right Light Series 2-Up Green is an energy-efficient alternative to the standard Green channel letter LEDs. Custom LED chips and advanced design make the RLS 2-Up Green one of the most desirable channel letter products on the market. Ideal for medium-large applications, the 2-Up Green houses two LED chips on a 2.5" board fitted with patented Quick Connect tabs to simplify installation and minimize labor.

FEATURES AND SPECIFICATIONS

- Patented Quick Connect tabs - easiest and fastest system to install on the market! No need for cutting or splicing wires
- Suitable for damp locations
- UL Recognized (US and Canada) and CSA approved
- Class 2 compliant
- 5-year warranty

2-Up Green

RIGHT LIGHT SERIES



DIMENSIONS

L 2.5" x W 1" x H .5"

ENERGY DATA

Input Power (V DC)	12
Watts per Foot	1.08
Lumens per Foot	38.40
Viewing Angle (°)	100
Color (nm)	516
Operating Temperature	(-40) to 60 °C / (-40) to 140 °F
LED L70 Lifetime (hours)	100,000



ORDERING INFORMATION

Example: GL-2-12-G

GL	2	12	G
Series	LEDs per Module	Input Voltage	Color
GL	2	12	G Green

PACKAGING SPECS

	Modules (feet)
Master Case	810 (270')
Inner Case	270 (90')
Tray	90 (30')

