

Project	Type
Catalog #	

DESCRIPTION


The Right Light Series 2-Up Red is an energy-efficient alternative to the standard Red channel letter LEDs. Custom LED chips and advanced design make the RLS 2-Up Red one of the most desirable Red products on the market. Ideal for medium-large applications, the 2-Up Red houses two LED chips on a 2.5" board fitted with patented Quick Connect tabs to simplify installation and minimize labor.

2-Up Red

RIGHT LIGHT SERIES

FEATURES AND SPECIFICATIONS

- Patented Quick Connect tabs - easiest and fastest system to install on the market! No need for cutting or splicing wires
- Suitable for damp locations
- UL Recognized (US and Canada) and CSA approved
- Class 2 compliant
- 5-year warranty



DIMENSIONS

L 2.5" x W 1" x H .5"

ENERGY DATA

Input Power (V DC)	12
Watts per Foot	2.16
Lumens per Foot	45.60
Viewing Angle (°)	110
Color (nm)	625
Operating Temperature	(-40) to 60 °C / (-40) to 140 °F
LED L70 Lifetime (hours)	100,000



ORDERING INFORMATION

Example: RLS-2-12-RX

RLS	2	12	RX
Series	LEDs per Module	Input Voltage	Color
RLS	2	12	RX Red

PACKAGING SPECS

	Modules (feet)
Master Case	810 (270')
Inner Case	270 (90')
Tray	90 (30')

