

<b>Project</b>	<b>Type</b>
<b>Catalog #</b>	

## DESCRIPTION

QubePAK2 is a wall-mounted LED luminaire designed for outdoor area lighting applications. Using a mere 67.6 Watts of power and delivering over 4,200 lumens, the QubePAK2 is an ideal replacement for 250 Watt metal halide wall pack fixtures. The QubePAK2's long L70 life expectancy of 70,000 hours will not only minimize or eliminate maintenance and replacement costs, but will also promote environmental restoration through reduced CO2 emissions and reduced waste/landfill. Backed by US LED's standard 5-year warranty, QubePAK2 is a sound investment in performance, longevity and contributing to the global green movement.

# QubePAK2™

Wall Pack Luminaire  
2-Qube, 120-277V Input



## FEATURES AND SPECIFICATIONS

- Standard 5-year warranty
- Low voltage Class 2 design
- Internal Qube LED module features advanced heat sink and thermal sensor technology
- Uses at least 70% less power than equivalent metal halide

## CERTIFICATION

- UL Listed USA and Canada File # E338791
- LM-80
- LM-79



### ENERGY DATA

Input Voltage (V AC)	120 - 277
System Level Power (W)	67.6
Delivered Lumens (Lm)	4,247
System Efficacy (Lm/W)	62.8
Correlated Color Temp (K)	5700K
LED L70 Lifetime (hrs)	70,000
Minimum CRI	70
Operating Temperature (°C)	-30 to 50

### SPECIFICATIONS

Dimensions (in)	18.3 x 9 x 9.6
Units/carton	1
Net Weight	14.9 lbs
Environmental Rating	Wet

## ORDERING INFORMATION

Example: DS-403U-1-UNV-QB-OS2-57-2-L

DS	403U	1	UNV	QB		57	2	
Series	Fixture Style	Variant	Input Voltage	Qube LED Array	LED Type	Color Temp	# of Qubes	Light Distribution Pattern
DS	403U	1	UNV	QB	OS1 OS2	57 5700K	2	RL Rectangular Long L Lambertian

Specifications and dimensions subject to change without notice.

DATASHEET 02.10.2012