

Emergency Exit Sign

Life Safety LED Lighting



Key Features

- Compact, low-profile design.
- Ultra-bright, energy-efficient LED technology.
- 6" illuminated red letters with 3/4" stroke.
- Snap out chevron directional indicators.
- Remote capable.

Construction

- Injection-molded thermoplastic ABS housing with UL94V-0 flame rating.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.

Electrical

- 120-277V dual voltage operation.
- Built-in 1.2V rechargeable Ni-MH battery for up to 90 minutes of emergency operation.
- Operating temperature: 0°C to 40°C (0°F to 104°F).

Mounting

- Easy snap mounting canopy for top or end mount.
- Universal knockout pattern on back plate for wall mounting.

Warranty

- Backed by a Five-Year Warranty (excluding battery at 2 years).

Product Overview

US LED's ESX1 emergency exit sign is the perfect solution for projects requiring code-compliant emergency signage. This emergency exit sign features a rechargeable battery backup for emergency operation and a switch for compliance testing.

Product Applications

- Building Entrances/Exits

Product Certifications

- UL Listed
- Complies with UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes
- Suitable for Damp Locations
- RoHS Compliant



Ordering Information

Example: **ESX1**

Model

- ESX1** Standard Exit Sign With Red Letters, and Battery Backup

Emergency Exit Sign

Life Safety LED Lighting



Dimensions

