

# Slim Dual LED Exit Sign Combo

## Emergency/Exit LED Lighting



### Key Features

- Ultra-long life, high performance white LED lamp heads.
- Adjustable LED lamp heads provide optimal spacing and light distribution.
- 6" illuminated red letters with 3/4" stroke.
- Single or dual face standard.
- (2X) 1W SMT LED lamp heads for emergency operation.

### Electrical

- 120-277V dual voltage operation.
- Built-in 3.6V rechargeable NiCd battery for up to 90 minutes of emergency operation.
- Remote capability up to 2W.
- Fully automatic two-rate charger will recharge a discharged battery in 24 hours.
- Operating temperature: 0°C to 40°C (0°F to 104°F).

### Construction

- Injection-molded thermoplastic ABS housing with UL94V-0 flame rating.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.

### Mounting

- Suitable for wall or ceiling mounting.
- Standard installation with universal J-Box mounting pattern.

### Warranty

- Backed by a Five-Year Warranty.

### Product Overview

US LED's slim emergency exit combo sign is the perfect solution for projects requiring emergency signage and lighting. In addition, the emergency exit light batteries can be paired with remote heads for optimal spacing and light distribution.

### Product Applications

- Building Entrances/Exits

### Product Certifications

- UL Listed
- Complies with UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes
- Suitable for Damp Locations
- RoHS Compliant



Example: **ESEM-PC-UNVL-2-RC**

### Ordering Information

ESEM	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
Series	Material	Input Voltage	# of Faces	Options
<b>PC</b>	ABS Plastic Housing	<b>UNVL</b> 120-277V	<b>2</b> Universal Single/Dual Faced	<b>RC</b> Remote Capability