

# Dual Head Emergency Unit

## Emergency/Exit LED Lighting



### Key Features

- Ultra-long life, high performance white LED lamp heads.
- Adjustable LED lamp heads provide optimal spacing and light distribution.
- (2X) 1.2W SMD LED lamp heads for emergency operation.

### Electrical

- 120-277V dual voltage operation.
- Built-in 3.6V 1000mAh rechargeable NiCd battery for up to 90 minutes of emergency operation.
- Operating temperature: 0°C to 40°C (0°F to 104°F).

### Construction

- Injection-molded thermoplastic ABS housing with UL94V-0 flame rating.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.

### Mounting

- Suitable for wall or ceiling mounting.

### Warranty

- Backed by a Five-Year Warranty.

### Product Overview

US LED's dual head unit is the perfect solution for projects requiring versatile emergency lighting. This emergency unit offers an ideal emergency operation with optimal spacing and light distribution.

### Product Applications

- General Emergency Lighting

### Product Certifications

- Complies with UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes
- Suitable for Damp Locations
- RoHS Compliant



Example: **EM-PC-UNVL-2-RC**

### Ordering Information

| EM        | <input type="text"/> | <input type="text"/> | <input type="text"/>    | <input type="text"/>        |
|-----------|----------------------|----------------------|-------------------------|-----------------------------|
| Series    | Material             | Input Voltage        | # of Lamp Heads         | Options                     |
| <b>PC</b> | ABS Plastic Housing  | <b>UNVL</b> 120-277V | <b>2</b> Two Lamp Heads | <b>RC</b> Remote Capability |