

USL1

LED Linear Strip Light | Selectable CCT & Wattage



Key Features

- The compact linear design makes it easy to install virtually anywhere you need lighting.
- Choose the perfect CCT and wattage that suits the setting with integrated switches.
- Motion sensing capabilities allow it to turn on and off as needed, providing convenient and energy-efficient lighting.
- Emergency back-up option available.

Electrical

- 120-277VAC input. 50/60Hz input.
- 0-10V dimming standard.
- Power factor: >0.98 and THD <20%.
- Operating temperature: -30°C to 40°C (-22°F to 104°F)

Mounting

- Ready to be suspended with adjustable cable or surface mounted with snap joints.

Construction

- Aluminum housing in a standard white finish that optimizes thermal management.
- Frosted acrylic diffuser designed for uniform light distribution, superior glare control, and improved aesthetics.
- End caps are high-impact injection molded PMMA material in a standard white finish.
- Standard 10' white power cord.

Optics

- Selectable CCT switch with choices of 3500K, 4000K, and 5000K.
- Industry-leading LEDs with ≥80 CRI.
- Lumen Maintenance: >161,000 hours (L70) ¹

Warranty

- Backed by US LED's industry-leading Ten-Year Warranty.

Project	Date
---------	------

Catalog Number	Type
----------------	------

Product Performance Summary

Lumen Output	Up to 6,106 lumens
Efficacy	Up to 152 LPW
CRI	≥ 80 CRI
Available CCT	Selectable CCT 3500K, 4000K & 5000K
Warranty	Ten-Year Warranty

Product Overview

The USL1 LED linear strip light is a modern lighting solution that offers exceptional performance and ease of use. This versatile strip features selectable CCT and wattage switches, allowing you to choose the perfect lighting for any setting. Moreover, it can be specified with motion-sensing capabilities to support occupant well-being and optimize energy usage. Designed to deliver brilliant illumination and clarity, the USL1 is built to be installed easily in any location, so your new lighting is up and running in no time.

Product Applications

- Self-Storage Facilities
- Educational Facilities
- Industrial/Warehouse
- Office Spaces
- Retail/Grocery
- Hallways/Displays

Product Certifications

- ETL Listed for US & Canada
- Complies with UL1598 and CSA 22.2
- DLC Listed
- Suitable for Indoor Damp Locations
- RoHS Compliant



Example: USL1-4-UNV-SCCT

Ordering Information


USL1	<input type="text"/>	<input type="text"/>	<input type="text"/>
Series	Size	Input Voltage	CCT
4	4 ft. Model: 25W/35W/45W	UNV 120-277V	SCCT Selectable CCT: 3500K, 4000K, and 5000K

Accessories	
B ²	Battery Back-Up
BM ²	Battery Back-Up & Internal Motion Sensor (On/Off)
BMS ²	Battery Back-Up & External Motion Sensor (Dimming/PhotoCell)
JB	Junction Box
JBMS	Junction Box & Motion Sensor
M	Internal Motion Sensor (On/Off)
30264	Adjustable Cable Kit (10 ft., 2 Qty.)


1. US LED product 'Lifetimes' refer only to the LED light engine, not the power source, and are based on IESNA TM21 Projected Lumen Maintenance methodology at a 25° C / 77° F ambient temperature. The lifetimes are solely meant to be a guide for expected LED degradation and not a warranty or predictive of their actual life, which can be affected by ambient temperatures and other factors. In accordance with IESNA TM-12-11, calculated values represent time durations that exceed six times NA LM-80-08 total test duration (in hours) for the device under testing (DUT) i.e. the packaged LED chip.
2. Only available with 4 ft. option.

Dimensions


Standard Side View



Standard Bottom View




Standard End View




Size	A	B	C	D	Net Weight
4 ft.	47.2 in. [1200 mm]	2.9 in. [75mm]	1.3 in. [33mm]	2.8 in. [72mm]	2.0 lbs. (0.9kg)

Battery Back-Up Side View



Battery Back-Up End View



Net Weight
4.0 lbs. (1.8kg)

USL1 shown with junction box and battery back-up options installed.




Performance Data

Luminaire Photometric Data

Model Number	USL1-4-UNV-SCCT 45
Issue Date	12/17/2022
IESNA	LM-63-2002
Lamp/CCT	LED/5000K
Total Input Watts	45.3
Total Lumens	6106.4
Efficacy	134.8

Luminous Intensity Distribution Diagram




Model	Wattage	System Level Power	Delivered Lumens	Efficacy	CCT	L70 Calculated Life
USL1-4-UNV-SCCT	25W	24.6W	3619.4	147.1 LPW	3500K	>161,000 Hours
		23.6W	3644.3	152.5 LPW	4000K	>161,000 Hours
		24.4W	3562.6	146.0 LPW	5000K	>161,000 Hours
	35W	35.4W	5044.6	142.5 LPW	3500K	>161,000 Hours
		34.7W	5244.3	151.1 LPW	4000K	>161,000 Hours
		36.0W	5062.9	140.6 LPW	5000K	>161,000 Hours
	45W	45.2W	6087.5	134.7 LPW	3500K	>161,000 Hours
		43.9W	6437.5	146.6 LPW	4000K	>161,000 Hours
		45.3W	6106.4	134.8 LPW	5000K	>161,000 Hours


Mounting Options

Surface Mount With Snap Joints

USL1 Snap Joints (2 Qty.)



USL1 Standard



USL1 With Junction Box
& Emergency Back-Up

Suspended Mount With Adjustable Cables

[30264] - USL1 Adjustable Cables (2 Qty.)



USL1 Standard



USL1 With Junction Box
& Emergency Back-Up