

# 27.9W LED Tubes

## T8 Type B Double-Ended



### Key Features

- Quick and easy LED upgrade for existing open or enclosed fixtures.
- Type B - Internal LED driver bypasses existing ballasts and eliminates the need for an external LED driver.
- Instant on - no delay or warm up time.

### Electrical

- 120-277VAC input.
- Power Factor: ≥0.90; THD: <20%
- Operating temperature: -20°C to 40°C (-4°F to 104°F).

### Warranty

- Backed by US LED's industry-leading Ten-Year warranty.

### Construction

- Available in 4 ft. length.
- Fully-sleeved frosted glass tube housing with PET film is shatter-resistant.
- Easy disposal, non-hazardous waste.

### Optics

- Industry-leading LEDs with 3500K, 4000K, and 5000K CCT (minimum 80 CRI).
- Full Illumination with >320° Beam Angle.
- Lumen Maintenance: 200,000 hours (L70)<sup>1</sup>

Project	Date
---------	------

Catalog Number	Type
----------------	------

### Product Performance Summary

Lumen Output	Up to 4,250 lumens
Efficacy	Up to 152 LPW
CRI	≥ 80 CRI
Available CCT	3500K, 4000K, or 5000K
Warranty	Ten-Year Warranty

### Product Overview

T8 Type B double-ended LED tubes are the perfect solution for upgrading existing fluorescent fixtures to LED technology without a comprehensive reinstall. These LED tubes offer quality illumination up to 200,000 hours (L70) and are backed by US LED's industry-leading Ten-Year Warranty.

### Product Applications

- Retail Stores
- Industrial/Warehouses
- Hallways/Corridors
- Classrooms
- Conference Rooms
- Storage Areas
- Office Spaces
- Convenience Stores

### Product Certifications

- UL Listed.
- DLC Listed.
- Suitable for indoor damp locations.
- RoHS compliant.



### Ordering Information

Example: ST1-4-UNV-4-27A-50-GL-DE

ST1							
Series	Variant	Input Voltage	Length	Wattage	CCT	Diffuser	Power Location
4	Standard	UNV	120-277V	4	4 ft.	27A	27.9W
				35	3500K	GL	Glass
				40	4000K		
				50	5000K		
						DE	Double Ended

1. Product 'Lifetimes' refer only to the LED light engine, not the power source, and are based on the Illuminating Engineering Society's TM21 Projected Lumen Maintenance methodology at a 25°C / 77°F ambient temperature. The lifetimes are solely meant to be a guide for expected LED degradation and not a warranty or predictive of their actual life, which can be affected by ambient temperatures and other factors.

# 27.9W LED Tubes

## T8 Type B Double-Ended



### Performance Data

Model	Input Voltage	CCT	Input Power	Lumen Output	Efficacy	CRI	L70 Calculate Life
<b>ST1-4-UNV-4-27A-35-GL-DE</b>	120-277VAC	3500K	27.9W	4,150	149 LPW	≥80	200,000 Hours
<b>ST1-4-UNV-4-27A-40-GL-DE</b>	120-277VAC	4000K	27.9W	4,200	151 LPW	≥80	200,000 Hours
<b>ST1-4-UNV-4-27A-50-GL-DE</b>	120-277VAC	5000K	27.9W	4,250	152 LPW	≥80	200,000 Hours

### Accessories

Model	Description
<b>LS-1-4</b>	LoneStar, 1 Tube Strip Fixture Housing
<b>LS-2-4</b>	LoneStar Tandem, 8' Single Strip Housing
<b>TSW1</b>	TwinStar, 2 Tube Strip Fixture Housing
<b>TWS1-T</b>	TwinStar Tandem, 8' Double Strip Housing
<b>TWS1-1</b>	TwinStar, 2 Tube Strip Fixture Housing With Accommodations For Occupancy Sensor
<b>TR-3-4</b>	TriStar, 3 Tube Strip Fixture Housing
<b>USQS-44</b>	QuadStar, 4 Tube Wide Body Strip Housing
<b>HBT1</b>	SixShooter, 6 Tube High Bay Fixture Housing
<b>HBT1-1</b>	SixShooter, 6 Tube High Bay Fixture Housing With Accommodations For Occupancy Sensor
<b>UCLL-24</b>	2x4 Housing with Ribbed Lens - Ceiling Mounted
<b>UCLLS-24</b>	2x4 Housing with Ribbed Lens - Surface Mounted
<b>LS-WG-48</b>	Wireguard Protection for LoneStar Strip Fixture Housing
<b>BCK-8-2-US</b>	1x8 Two Lamp Retrofit
<b>BCK-8-4-US</b>	1x8 Four Lamp Retrofit
<b>RKSR-232TAN-WINST</b>	8' to 4' Conversion Kit
<b>USVT-24</b>	4' Vapor Tight Housing
<b>USVT-44</b>	8' Vapor Tight Housing